



Getting Started

Before installation, check the product for any shipping damages. If you find damages, do not install and contact your dealer or ICO.

Electrical Connections

All wiring should be done by a qualified licensed electrician

- ⚠ **Caution** Read and follow all instructions before installing this LED mirror.
- ⚠ **Danger** Shut off power before wiring the mirror.
- ⚠ **Warning** Requires 120VAC 20 Amp GFI protected circuit.

IMPORTANT SAFETY INSTRUCTIONS

⚠ **Warning**

To reduce the risk of burns, fire, electric shock or injury to persons. Use this furnishing only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer. Never drop or insert any object into any opening. Do not use outdoors.

GROUNDING INSTRUCTIONS

⚠ **Danger**

Risk of electric shock. Connect this furnishing to a properly grounded circuit only.

This product must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the product.



For an electrical hardwire option, the LED mirror must be wired to a 20 Amp GFI (Ground Fault Interrupter) protected circuit when used in bathrooms and all other locations as per your respective local Electrical Code.

REQUIRED TOOLS & MATERIALS

PARTS INCLUDED



INSTALLATION & POWER OUTLET GUIDE



- a** - distance between hang holes
- b** - height - top of the mirror to hang hole
- c** - height - top of the support to hang hole

Power cord length is 39 3/8" (1000mm) but do an actual measurement, especially if the power outlet or junction box is farther than 30" (762mm).


Measure and determine overall mirror dimensions as well as "a", "b" & "c" (see diagram) before installation.

All dimensions and specifications in the table below are approximate and may vary without prior notice.

Use your actual product measurement for accuracy.

Model #	a (distance between hang holes)	b (height - top of the mirror to hang hole)	c (height - top of the support to hang hole)	Product Dimension
IG1130	"19 5/8" 500"	"11 5/8" 295"	"3 3/4" 95"	"29 1/2" x 35 3/8" x 1 1/8" (750mm x 900mm x 30mm)"

*Download the specific model's tech spec sheet on our website for other measurements



Color Shading Guide

- Ideal location of the electrical outlet or junction box.
- Location not advisable! Moreover, power cord must not cross or be over any part of this shaded part.


**Diagram is for electrical outlet located behind the mirror. If electrical outlet is to the side or at the bottom/top of the mirror, always consider the length of the power cord (see previous page for measurement) and the darker shades in these diagrams where cord and/or plug must not cross over or be on top of.*

Mirror Installation


- 1 Unpack your mirror and set it on the floor – ensure you lay out floor protection – cardboard, towel etc.
- 2 Measure mirror dimensions before proceeding with installation.

* All dimensions in the Technical Specifications Sheet are approximate and may change without notice.


- 3 Mark the position of the mirror on the wall.
Keep at least 3" distance between the bottom end of the mirror and the top of the faucet (if installed over a sink or vanity top).




- 3 Measure the center of the holes (A) and mark the drilling locations. Ensure the mirror is level (B).





- 5 Pre-drill and install drywall anchors. Screw the supplied screws into the anchors. Leave a gap of 6-8mm between the head of the screw and the wall.



- 6 For plugin installation - plug in the mirror to the grounded outlet.



For hardwired installation - cut off the power plug, then use the wire connector to connect to external power supply.




*Junction box is not included




Make connection | Neutral to white
Live to black
Ground to green

Both installation options can be connected and controlled with a light switch.

- 7 Place the mirror against the wall (and the screws) and slide down as shown in B.



Operating Instructions

-  Touch to turn light and defogger on/off. (The heating pad/defogger auto turns off after one hour).
-  Press and hold to adjust color temperature.
-  Press and hold to adjust the brightness. Touch will increase/decrease (with 4 preset brightness levels).

This LED mirror has brightness and color temperature memory settings capability. Turning off (whether through touch or light switch) saves the last settings used.